Accessible Taxicab Inspection Checklist

ITEM		DATA/NOTES
Inspection Date:		
Inspector Name:		
Medallion Owner:		
Medallion #:		
Phone:	Cell:	
VEHICLE MAKE/MODEL/YEAR:		
RAMP		
Slope [If height of the vehicle floor from which ramp is deployed is 3 inches or less		
above a 6-inch curb, slope should not exceed 1:4 (36 CFR §1192.23 (c) (5))]:		
Length:		
Width [Should be not less than 30 inches wide (36 CFR §1192.23 (c) (2))]:		
Edge Protection [Side edges of ramp should be not less than 2 inches high (36		
CFR §1192.23 (c) (4))]:		
Other [Transition edges at top & bottom of ramp should not exceed 1/4 inch (if vertical		
edge) or ½ inch (if beveled edge) (36 CFR §1192.23 (c) (3))]:		
ENTRYWAY & WHEELCHAIR SECUREMENT AREA		
Doorway Height [should be not less than 56 inches (36 CFR §1192.25 (c))]:		
Securement Area Height [should be not less than 56 inches		
(36 CFR §1192.29 (f))]:		
Securement Area Width [should be not less than 30 inches		
(36 CFR §1192.23 (d) (2))]:		
Securement Area Depth [should be not less than 48 inches		
(36 CFR §1192.23 (d) (2))]:		
Wheelchair Securement Devices [should be provided in addition to		
lap/shoulder belts (36 CFR §1192.23 (d) (1))]:		
Other:		

Disclaimer: This checklist is provided as an aid in assessing accessibility of vehicles equipped with ramps, not lifts. While based on Americans with Disabilities Act (ADA) Standards, this checklist should be used in conjunction with, not as a substitute for those standards. The medallion owner bears full responsibility for ensuring compliance with ADA Standards, and should not purchase, lease, or otherwise acquire a vehicle for taxicab use until certain it meets all applicable ADA Standards.

The U.S. Architectural and Transportation Barriers Compliance Board's accessibility guidelines for vehicles are codified at 36 CFR Part 1192. The implementing ADA regulations ("Standards") of the U.S. Department of Transportation are codified at 49 CFR Part 38.