





## Sustainable Design and Development

## Introduction

In compliance with Section 22.23 of the Cambridge Zoning Ordinance, the following chapter outlines the LEED certification goals for the Project and describes the strategies employed to meet the targeted LEED requirements and credits based on this stage of design development. The current LEED Scorecard is presented as Figure 4.1Attachment 3 includes an affidavit by the project LEED Accredited Professional.

The Project will register under the LEED v4 BD+C Multifamily Midrise program. It is tracking Gold level certification (65+ points). The following is a summary of points per category:

| Integrative Process          | [2 points]    |                       |
|------------------------------|---------------|-----------------------|
| Location and Transportation  | [15 points]   |                       |
| Sustainable Sites            | [3.5 points]  | [3 possible points]   |
| Water Efficiency             | [5 points]    | [2 possible points]   |
| Energy and Atmosphere        | [18.5 points] | [5 possible points]   |
| Materials and Resources      | [3.5 points]  | [3.5 possible points] |
| Indoor Environmental Quality | [8 points]    | [3 possible points]   |
| Innovation                   | [4 points]    |                       |
| Regional Priority            | [3 points]    |                       |

Total Points [62.5 points] [16.5 possible points]

## Conformance with Article 22.23

## **Integrative Process**

The Project is currently targeting 2 points total in the Integrative Process (IP) category and 1 point for exemplary performance.

IP Credit Integrative Process

Option 1. Integrative Project Team (1 point)

This credit will be earned with the experienced project team's capabilities and involvement throughout the design and construction process as well as at regularly held project team meetings. In addition to the Developer, the project team includes the Architect, Mechanical Engineer, Civil Engineer, Landscape Architect, Energy Modeler, Sustainability Consultant, and Structural Engineer. All of these team members will work together from design through construction with the goal of achieving a durable, energy efficient, sustainable and healthy project.

Option 2. Design Charrette (1 point)

Building upon the Integrative Project Team Credit above, a full day charrette was held in April 2018. In addition to the Developer, the Charrette was attended by the Architect, Mechanical Engineer, Civil Engineer, Landscape Architect, Energy Modeler, Sustainability Consultant, and Structural Engineer.

Option 3. Trades Training (1 point)

In addition to the Charrette during the design phase, eight hours of training on the green aspects of the project will be conducted in the beginning of construction for the trades. The training will focus on how the trades can contribute to achieving each LEED for Homes prerequisite and attempted credit.

## **Location and Transportation**

The Project is currently targeting 15 points in the Location and Transportation (LT) category and 1 point for exemplary performance.

LT Prerequisite Floodplain Avoidance (Required)

50 CambridgePark is located on a previously developed urban site in Cambridge, MA. It is located within the flood hazard area, but because it is being developed on a previously existing site, and will comply with required local flood provisions the project will comply with this prerequisite.

LT Credit Site Selection

Option 1. Sensitive Land Protection

Path 1. Previously Developed (4 points)

The Project Site is located on a previously disturbed lot . It is a 100% previously developed urban site in Cambridge, MA and therefore complies with the requirement of this credit.




Option 2. Infill Development (2 points)

The project is sited in an urban location and is considered an infill site with development on all sides of its boundaries, complying with the requirements for this credit.

## LT Credit Bicycle Network and Storage (1 point)

The project has bicycle storage within 200 yards of a bicycle network that connects to more than ten community resources, including an employment center, and MBTA bus and Red Line transit stops via the Greenway Bike Path, Fitchburg Cutoff Bikepath, Minuteman Commuter Bikeway and the Alewife Hubway bike sharing station at the Alewife T Station.. There will be 326 long term bike spaces and a minimum of 28 short term spaces for the 687 occupants.



## LT Credit Compact Development (3 points)

The project proposes 299 units and 166 units per acre which well exceeds the 35 units per acre threshold for this credit.

LT Credit Community Resources (2 points + 1 point for exemplary performance) Located within ½ mile walking distance to 16 community resources earns the project an extra point in exemplary performance.

## 50 Cambridge\_Community Resources.xlsx

|   | 1 50 | CambridgePark Dr. Cambridge, MA |                       |
|---|------|---------------------------------|-----------------------|
| Category  |      | Name of establishment           | Dist from project (mi |
| Family Entertainment                                | 1    | Apples Cinema                   | 0.5                   |
| Venue (Theatre, Sports)                             |      |                                 |                       |
| Bank  | 1    | Eastern Bank                    | 0.4                   |
| Dalik   | 1    | Wainwright Bank & Trust         | 0.4                   |
| Community or Civic Center                           | 1    | Arthur Murray Dance Center      | 338 ft                |
| Continuity of Civic Center                          | 1    | Francis J. McCrehan Pool        | 0.3                   |
| Convenience Store                                   | 1    | Alewife T Station News          | 0.2                   |
| Convenience Store                                   | 1    | Quick Bite                      | 0.2                   |
| Daycare Center                                      | 1    | Panda Bilingual Daycare         | 36 ft                 |
| Daycare Center                                      | 1    | Cambridge Kinder Care           | 0.1                   |
| Hair Care   |      |                                 |                       |
| Fitness Center or Gym                               | 1    | Core Power Yoga                 | 0.4                   |
| l   | 1    | Laundry Town                    | 0.3                   |
| Laundry or Dry Cleaner                              | 1    | Rigazio's Dry Cleaners          | 0.4                   |
| Library   |      |                                 |                       |
| 100000000 • 1                                       | 1    | Alewife Brook Reservation       | 0.2                   |
| Public Park   |      | Alewire Brook Reservation       | 0.2                   |
| Social Services Center                              |      |                                 |                       |
| Pharmacy  |      |                                 |                       |
| 50000000000000000000000000000000000000              | 4    | New Yor Challen Town & Dallen   |                       |
| Police Station                                      | 1    | Alewife Station Transit Police  | 0.2                   |
| Post Office   |      |                                 |                       |
|   | 1    | Light of Life Church            | 0.2                   |
| Place of Worship                                    | 1    | Church in Cambridge             | 262 ft                |
|   | 1    | Bertucci's of Alewife           | 292 ft                |
| Restaurant  | 1    | Summer Shack                    | 338 ft                |
|   | 1    | Sunrise Learning Academy        | 135 ft                |
| School  |      |                                 |                       |
| Communication                                       | 1    | Trader Joes                     | 0.5                   |
| Supermarket   | 1    | Whole Foods                     | 0.5                   |
|   | 1    | Modell's Sporting Goods         | 0.4                   |
| Other Neighborhood-<br>serving Retail               | 1    | TJ. Maxx                        | 0.5                   |
|   | 1    | Dicerna Pharmaceuticals         | 0.1                   |
| Other Office Building or<br>Major Employment Center | 1    | BitSite Tech                    | 0.1                   |
|   | 25   | TOTAL Community Reso            | Urone                 |

LL Credit 5

## LT Credit Access to Transit (2 points)

Located on an urban site in Cambridge, MA, the project site is in close proximity to many options of public transportation. It is within a mere 200 hundred feet from the Alewife T Red line and ¼ mile of several bus routes with a combined weekday trips and 2weekend day trips exceeding 125 rides, qualifying for 2 points under this credit.

## Sustainable Sites

The Project is currently targeting 3.5 points total in the Sustainable Sites (SS) category.

## SS Prerequisite Construction Activity Pollution Prevention (Required)

The Construction Manager (CM) will provide and shall implement an Erosion and Sedimentation Control (ESC) Plan and for construction activities related to the demolition of existing site elements and construction of the new building. The ESC Plan shall conform to the erosion and sedimentation control requirements of the 2012 EPA Construction General Permit (ESC) and specific municipal requirements for the City of Cambridge.

## SS Prerequisite No Invasive Plants (Required)

The project team is specifying plantings for the project that are identified by the local extension services as either native or non-invasive. While the LHMR program requires avoidance of invasive plantings and awards projects installing drought tolerant species, the project team has set a more rigorous goal by including strategies from the USGBC's Sustainable Sites Initiative (SITES®). While areas designated for outdoor seating, dining, recreation, and socializing are integral to the design, the landscape will support local fauna and limit reliance on irrigation.

## SS Credit Heat Island Reduction

Option 1. Shading (2 points)

The project has designed for reduced heat island effects on the site through the use of Energy Star qualified high solar reflective and green roof spaces. Hardscapes will be shaded where possible such that approximately 85% of the project is either shaded or non-absorptive material.

## SS Credit Nontoxic Pest Control (2 points)

The project will integrate design strategies to mitigate pest control, such as excluding wood siding, sealing external cracks and joints with caulking and installing pest-proof screens. The Developer implements a thorough Integrated Pest Management Plan (IPM) throughout their buildings which includes an educational and awareness component for residents and building managers.

## Water Efficiency

The Project is currently targeting 5 points total in the Water Efficiency (WE) category.

WE Prerequisite Water Metering

Case 2. Multifamily (Required)

The project will install a water meter for the entire building, meeting the requirement of this prerequisite. Hanover is exploring additional metering options to monitor, track, and record water usage for competition amongst its dorms (similar to its energy savings competitions).

Prescriptive Path

WE Credit Indoor Water Use

Case 2. Multifamily and Midrise (5 points)

The design of the plumbing systems will include the use of low flow fixtures to reduce the water use of the building. In residential units, low flow WaterSense<sup>TM</sup> labeled shower heads with less than 1.5 gallons per minute flow rate will significantly reduce residential water use. Additionally, residential WaterSense labeled lavatory faucets which will operate at 0.5 gallons per minute or less will be installed further improving water efficiency. The project will also install WaterSense labeled toilets with a flush rate of 1.28 gallons per flush or less.

WE Credit Outdoor Water Use (3 points)

The project will not include any turf and the vegetated areas both at the street level and on building roofs will be planted with native and/or adapted vegetation. Irrigation will be installed with high efficiency features such as: rain sensors, zone controls, high-efficiency nozzles, pressure regulating devices, and drip irrigation in beds. LEED points for the WE section will most likely be tallied using the overall water reduction calculator, which allows the university to utilize a baseline target for performance goals.

## Energy and Atmosphere

The Project is currently targeting 18.5 points total under the LEED v4 Multifamily Midrise, Energy and Atmosphere (EA) category. The Rating System offers two pathways for compliance with the prerequisite and credits. The pathways are compliance through demonstrated performance (ASHRAE 90.1 modeling) or compliance through prescriptive measures. This project will comply with EA prerequisites and credits by demonstrating performance with a whole building, ASHRAE 90.1 energy model.

EA Prerequisite Minimum Energy Performance (Required)

The project is exceeding requirements of ASHRAE 90.1-2010 Sections 5.4, 6.4, 7.4, 8.4, 9.4 & 10.4.

EA Commissioning

Option 2. Commissioning with using Prescriptive Path (Required)

This project will comply with the Option 2 Cx using Prescriptive Path by doing all of the following:

- b) L-H Thermal Enclosure Inspection Checklist (ESv3r2 Sec. 2,3,5)
- "c) Cx of central systems meet LEED NC performance testing & ongoing maintenance for central commercial HVAC & DHW"
- d) Total duct leakage <8cfm25/100sf enclosure
- e) Duct leakage to outside <4cfm25/100sf enclosure (6cfm <1200sf)

## EA Prerequisite Energy Metering

Case 2. Multifamily (Required)

The project will install a whole-building gas meter and an electric sub-meter in residential and common areas complying with the requirement of this credit.

EA Prerequisite Education of Homeowner, Tenant, or Building Manager (Required) The key to a successful project is that the building manager be the center of operations. The project team will assemble an operations and training manual for the building manager, and will coordinate an orientation with appropriate system vendors. In collaboration with the project design team, the Developer will also develop a tenant operations and training manual to be provided to residents during orientation.

## EA Credit Annual Energy Use (18.5 points)

A primary project goal is to design and build an exemplary structure with extremely low energy consumption and low life cycle costs. The building is designed to meet multiple energy codes and standards, including those set by the City of Cambridge and ASHRAE Standard 90.1. Energy efficiency strategies will include:

- High performance envelope
- 2. Reduced Lighting Power Density in common areas, corridors, and dorms
- Lighting Controls beyond that required by code
- Unitized apartment ventilation meeting ASHRAE 62.2
- 5. Reduced fan power, high performance heating and cooling units and distribution controls
- 6. Low-flow plumbing fixtures
- 7. Energy Star certified appliances where applicable.

All mechanical, electrical, and plumbing (MEP) equipment shall be of the highest quality to minimize maintenance while providing long useful life and high operating efficiencies. The HVAC systems will be "right-sized" to match the heating and cooling loads, with no oversizing, and distribution systems will be compact without compromising occupant comfort. To ensure efficient operations and comfort, comprehensive commissioning of the central HVAC systems, domestic water heaters, lighting control and electrical systems will be conducted. Thermal insulation levels will ultimately be selected based on energy model outputs and whole-building performance metrics.

LEED v4 MFMR calculates energy cost savings as compared to ASHRAE 90.1 -2010; the project is tracking to obtain a minimum of 15%-20% below a baseline building based on ASHRAE 2010. However, the minimum building energy standard that serves as the baseline for this project will be ASHRAE 90.1 Energy Standard for Buildings, Except Low-Rise Residential Buildings, 2013 Edition. Project team goals and decisions are based upon this more rigorous energy modeling assessment. The project will also follow the International Energy Code 2015 with amendments based on Massachusetts Stretch Energy Code. The City of Cambridge has adopted the MA Energy Stretch Code (Appendix AA to 780 CMR: State Board of Building Regulations and Standards). The MA Energy Stretch Code requires new buildings over 100,000 SF to demonstrate an energy cost reduction of a minimum 10% in comparison to ASHRAE 90.1 2013.

Hanover intends to exceed this minimum target with 12% to 15% energy cost

reduction in comparison to ASHRAE 90.1 2013 by constructing a high performing, air tight envelope with high efficacy lighting, appliances and equipment. LEED v4 MFMR credits projects with high occupancy per square foot. In addition to the 13 points earned with the ASHRAE savings, the project earns 7.5 addition points through the homes size adjustment calculation.

## Materials and Resources

The Project is targeting 3.5 points total in the Materials and Resources (MR) category.

MR Prerequisite Certified Tropical Wood (Required)

The project specifications will outline a preference for non-tropical, reused or reclaimed, or Forest Stewardship Council (FSC) or USGBC-approved equivalent products and will require submittals for all wood products to indicate the country of origin of the wood. If a tropical wood is specified, appropriate documentation and chain of custody will be required.

MR Prerequisite Durability Management (Required)

The project team will demonstrate that all minimum durability planning strategies mandated by regulatory agencies and LEED will be designed and implemented effectively. Building durability goals will be met through enhanced building enclosure, component systems, and material selection. Resource efficiency will be met by specifying and installing materials of recycled content and local sourcing when available.

MR Credit Durability Management Verification (1 point)

The owner has retained a LEED Green Rater to assist the contractor in ensuring the delivery of a durable building and verify the ENERGY STAR for Homes version 3 water management system builder checklist items executed.

MR Credit Environmentally Preferable Products (2 points)

The project specifications will require primary materials, such as concrete and drywall, to be extracted, harvested and manufactured within a 100-mile radius of the project site. High recycled content, minimum 25% postconsumer and/or 50% postindustrial waste recycled content, will also be pursued for materials, including concrete, insulation, counters and flooring. The project team is utilizing resources such as The Cradle to Cradle Products Program and The Health Product Declaration Collaborative to assess materials and finishes. Cabinets will be supplied by an Extended Producer Responsibility designated manufacturer.

MR Credit Construction Waste Management (1 point)

The construction management company has provided a demolition management plan including strategies for removing debris from the site. Prior to the onset of construction, the CM will prepare a Construction Waste Management plan, and provide monthly logs to the Applicant and the sustainability consultant. While the LEED v4 workbook calculates points for waste reduction as compared to a baseline allowance, a recent Credit Interpretation Request (CIR) allows multifamily building to use diversion reports to show compliance. This project will maximize construction debris that will be diverted from landfills and incinerators. In addition, the waste management logs will sort by material and show a minimum of four materials being

## **Indoor Environmental Quality**

The Project is currently targeting 8 points total in the Indoor Environmental Quality (IEQ) category.

EQ Prerequisite Ventilation (Required)

Local Exhaust

Each apartment and dorm room must be provided with adequate exhaust for local points of contaminants, such as bathrooms and kitchens, as required by ASRHAE 62.2-2010. The project will provide adequate exhaust with high efficacy fans. All local exhaust systems will be ducted directly to the outside.

Whole Unit Mechanical Ventilation (Required)

Each apartment must be provided with sufficient outdoor air as required by ASHRAE 62.2-2010. The project will provide sufficient outdoor air as required to each apartment with a continuous unitized exhaust fan.

Non Unit Spaces

The project is designed to meet the minimum requirements of ASHRAE Standard 62.1 – 2010 Sections 4 through 7 for all non-unit spaces.

EQ Prerequisite Combustion Venting (Required)

The project will provide sufficient exhaust for combusting appliances such as kitchen ranges, and water heaters. In addition, carbon monoxide sensors will be provided to each apartment and sleeping areas.

EQ Prerequisite Garage Pollutant Protection (Required)

The project will have an enclosed garage that will be designed to meet the following:

- a) All air handling equipement serving conditioned space located outside fire-rated envelope of the garage
- Tightly seal shared surfaces between the garage and conditioned spaces, bases of walls, including interstitial space, penetrations, and weather-stripped doors
- c) Install CO monitors in conditioned spaces with access to garage.

## EQ Prerequisite Radon-Resistant Construction (Required)

Cambridge, MA is located in a high risk area for Radon according to the US EPA. The project team will incorporate radon mitigation measures into design in construction which include these five components: 1) a gas-permeable layer; 2) heavy-gauge plastic sheeting; 3) sealing and caulking of all penetrations through the concrete slab; 4) vent pipe that exhausts gases to the outside through side wall or roof; and 5) electrical outlet near vent piping.

EQ Prerequisite Air Filtering - Good Filters (Required)

Minimum MERV 8 filters will be provided on all recirculating space conditioning systems, and MERV 6 filters will be provided on all mechanically

supplied outdoor air systems with 10 feet or more of ductwork supplying apartments and dorm rooms.

EQ Prerequisite Environmental Tobacco Smoke (Required)

Smoking will be prohibited in all areas of the building and outside the building except in designated smoking areas located at least 25 feet from all entries, outdoor air intakes and operable windows.

EQ Prerequisite Compartmentalization (Required)

Each residential apartment will be compartmentalized to minimize leakage between units. Uncontrolled pathways for indoor air pollutants between units will be reduced by sealing penetrations in walls, ceilings, and floors and by sealing vertical chases adjacent to the units.

Acceptable sealing of residential units will be demonstrated by blower door testing. The procedure described by RESNET will be used to demonstrate compliance with an allowable maximum leakage of 0.23 cfm50 per square foot (0.07 cmm50 per square meter) of enclosure (i.e., all surfaces enclosing the apartment, including exterior and party walls, floors, and ceiling). The owner has retained a RESNET accredited provider and rater to perform these air infiltration tests.

EQ Credit Contaminant Control for multifamily projects (1 point)

To reduce the spread of dirt and related contaminants into the building, exterior entryways to common areas will have a permanent walk off mat at least 10 feet long. (0.5 points)

Ducts and vents will be sealed to minimize contamination from construction debris. The third party Green Rater will verify this strategy during all phases of construction. Prior to occupancy the building will undergo a 48 hour flush out with windows open (in accordance with weather and safety) and fans running continuously. Filters will be replaced after this process which is intended to expedite off gassing of building materials and finishes for enhanced indoor air quality. (0.5 points)

EQ Credit Balancing of Heating and Cooling Distribution Systems

Case 1. Forced-Air Systems

Option 1 & 2 (2 points)

This project earns 1 point as a multifamily building with average sized units under 1,200 sf. Additionally, the supply air flow rates will be tested by a third party balancing contractor to demonstrate  $\pm$  20% (or  $\pm$  25CFM) of the calculated values from the ACCA Manual J room by room load sizing.

EQ Credit Combustion Venting (2 points)

A sealed, direct vented fireplace is planned for the Clubhouse, which will comply with the requirements of this credit.

EQ Credit Enhanced Garage Pollutant Protection

Option 1. Exhaust Fan in Garage (1 point)

The project will meet ASHRAE 62.1-2010, use appropriate controls, and test pressure differential to meet the credit.

## EQ Credit Low-Emitting Products (1.5 points)

Interior finish materials such as paintings and coatings, adhesives and sealants, and flooring will be verified for low VOC content that will meet requirements of CA Section 01350.

## EQ Credit No Environmental Tobacco Smoke (1 point)

Smoking will be prohibited in all areas of the building. The prohibition will be communicated to residents through the building agreement and training session.

## Innovation

The Project is currently targeting 4 points total in the Innovation (IN) category.

IN Prerequisite Preliminary Rating (Required)

LEED for Homes Midrise Multifamily requires project teams to take the essential first step to sustainability planning with a Preliminary Rating during the design phase. The first rating was conducted at a sustainability kick off meeting on March 16, 2018 with subsequent updates to present date.

IN Credit Innovation

Option 3. Exemplary Performance (3 points)

Exemplary performance in Integrative Process (IP) by achieving all three strategies (1 point).

Exemplary performance in LT Access to Transit (1 point)

Exemplary performance with access to 20+ LT community resources (1 point).

IN Credit LEED Accredited professional (1 point)

At least one principal participant of the project team will provide their LEED Accredited Professional (AP) Homes certificate to facilitate team integration through the certification process.

## **Regional Priority**

The Project is currently targeting 3 points in Regional Priority (RP) category.

RP Credit Regional Priority (3 points)

The project can target a number of Regional Priority credits. The project team will be evaluating the options to determine which one best fits the sustainability goals for the project currently the following credits are anticipated:

Annual Energy Use exceed 15 point threshold in Climate Zone 5 (1 point)

Balance Heating & Cooling Systems (1 point)

Access to Transit (1 point)

Heat Island Reduction exceed 2 point threshold (1 point)



TRUE

## LEEDv4 Multifamily Midrise Project Checklist



50 CambridgePark 50 CambridgePark Drive Cambridge, MA 02139 5/7/2018

Updated by Lauren Hildebrand, SWA

**Multifamily Midrise** 

| IP: II | NTE   | GR/  | TIV   | /E PR  | OCESS   |  |                       |                             |
|--------|-------|------|-------|--|---|--|-----------------------|-----------------------------|
| Υ      | ?     | N    |       | Max  |   |  |                       |                             |
| 2      | 0     | 0    | Final | 2*   | IP. Integrative Process   | Notes:   | Responsible<br>Party: | 3/16/17 Meeting<br>Comments |
| 1      |       |      |       | 1  | Option 1. Integrative Project Team 3 skill sets; involved in 3 phases; + monthly meetings   | Meeting #1: 3/16/18<br>Meeting #2: 4/13/18<br>Provide design meeting minutes;<br>ongoing                   | Hanover; Cube3        |                             |
|        |       |      | 1 [   |  | and/or  | I  | 1                     |                             |
| 1      |       |      |       | 1  | Option 2. Design Charrette 1 full-day or 2 half-days; 3 skill sets; no later than DD  | Can count 3/16/18 as first part.<br>Meeting #2 4/13/18   | Hanover               |                             |
|        |       | n/a  |       | 1  | and/or Option 3. Trades Training 8+ hrs total w/ Plumber; HVAC; Insulator; Framer; Air Sealer   | To be Completed on Site; ID point  | SWA                   |                             |
| 2      | 0     | 0    | ] [   | 2  | SUBTOTAL  |  |                       |                             |
| LT: I  | LOC   | ATIO | N     | AND  | TRANSPORTATION  |  |                       |                             |
| т      | F     | NA   | Final |  | LT-F. Floodplain Avoidance (meet one)   | Notes:   | Responsible<br>Party: | Plan Review Comments        |
| F      | ALSI  | É    | 11    | red  | a) Project is not built on land within a flood hazard area; or  | NA   |                       |                             |
| -      | TRUE  |      | П     | Prereq   | b) If in flood hazard area, site is previously developed; or  | Previously developed   |                       |                             |
|        | TRUE  |      | Ш     |  | c) If in flood hazard area, built per flood provisions  | Confirm flood provisions   | BSC                   |                             |
| Y      | ?     | N    | 1     | Max  | ľ   |  |                       |                             |
| 0      | 0     | 0    | 1     | 2000   | LT-ND. LEED for Neighborhood Development  | Notes:   | Responsible Party:    | Plan Review Comments:       |
|        |       | n/a  |       | 15   | ND v3 Stage 2 or 3 or ND v4 Certified Plan or Certified Project   |  |                       |                             |
|        |       |      | 1 [   |  | or  |  | Responsible           | D. D                        |
| 8      | 0     | 0    | ]     | 8*   | LT-SS. Site Selection   | Notes:   | Party:                | Plan Review Comments:       |
| 4      |       |      |       | 4  | Option 1. Sensitive Land Protection (meet one Path)  Path 1. Previously Developed  75% of buildable site is previously developed  or                              | 100% of total site buildable land<br>area (1.82 acres) previously<br>developed                             |                       |                             |
|        | n/a 3 |      | 3     | <ul> <li>Path 2. Avoidance of Sensitive Land (meet all of these)</li> <li>a) Not prime or unique farmland</li> <li>b) Not public parkland prior to acquisition</li> <li>c) Not in a flood hazard area</li> <li>d) Not on land identified as habitat for endangered species</li> <li>e) Not within 50ft of wetlands (or more stringent local reqm't)</li> <li>f) Not within 100 ft of water bodies</li> </ul> |   |  |                       |                             |
| 2      |       |      |       | 2  | Option 2. Infill Development 75% of land within 0.5mi of site is previously developed; water/public parks exempt from calc. Exception available if population<20k | 100% of project boundary previously developed  | SWA                   |                             |
| 1      |       |      |       | 1  | and/or Option 3. Open Space Within 0.5mi of public open space at least 0.75 acres; or create public open space onsite. 1 larger park or 2 smaller OK and/or       | Alewife Brook Parkway .06mi  | SWA                   |                             |
| 0      | 0     | n/a  |       | 1  | Option 4. Street Network Intersection density of 90 intersections per sq mile (street/sidewalk)   | Earned on 130 Cambridge (barely) - should earn here  | SWA                   |                             |
| 1      |       |      | ] [   |  | Option 5. Bicycle Network and Storage   |  |                       |                             |
|        | TRUE  |      |       | 1  | Within 200yd of network connecting to any of: 10 uses; school; employment center; rail, ferry, or bus rapid transit; and  | Confirm bike lanes; connection to Minuteman/Greenway/Fitchburg/H ubway bikeways; site plan shows bike path | SWA                   |                             |
| 1      | TRUE  | E    |       |  | b) Provide long-term storage for 30% of occupants; and  | Provide 206 long-term spaces; 326 in plans   | Cube3/Hanover         |                             |

c) Provide short-term bike storage for 2.5% of occupants (min 4)

plan shows 28?

Provide 18 short-term spaces; site

Cube3/Hanover

| 3    | 0  | 0     | 3   | LT-CD. Compact Development   | Notes:  | Responsible Party:            | Plan Review Comments:  |
|------|--|-------|---|--|---|-------------------------------|------------------------|
| 3    |  |       | 3*  | Lowrise: Achieve 7 (1pt), 12 (2pt), or 20 (3pt) dwelling units/acre<br>Midrise: Achieve 30 (1pt), 55 (2pt), or 80 (3pt) dwelling units/acre  | 299 units per 1.8 acres buildable land area (confirm total acreage) = 166 DU/acre                     |                               |                        |
| 2.0  | 0.0  | 0     | 2   | LT-CR. Community Resources   | Notes:  | Responsible Plan Review       |                        |
| 2.0  | 2* Within 0.5mi of 4-7 (1pt), 8-11 (1.5pt), or 12+ (2pt) resources |       | Within 0.5mi of 4-7 (1pt), 8-11 (1.5pt), or 12+ (2pt) resources | 12+ community resources w/in .5 miles  | SWA   |                               |                        |
| 2.0  | 0.0  | 0     | 2 LT-T. Access to Transit                                       |  | Notes:  | Responsible Plan Review Commo |                        |
| 2.0  |  |       | 2*  | Within 0.25mi walk of bus or 0.5mi of ferry/rail/BRT; see Comment  | 300ft from Red line; various bus<br>.2mi (confirm 360 weekday/216<br>weekend min daily transit trips) | SWA                           |                        |
| 15.0 | 0.0  | 0.0   | 15  | SUBTOTAL   |   |                               |                        |
| 26.0 | Suet   | ainal | ole Site  | c  |   |                               |                        |
| т    | F  | NA    | -   | SS-P. Construction Activity Pollution Prevention   | Notes:  | Responsible Party:            | Plan Review Comments:  |
| T    | RUE  |       | -   | a) Stockpiled and protected soil   | Provide SWPPP reports   | BSC BSC                       |                        |
|      | RUE  |       |   | b) Controlled runoff path and velocity   | Provide Plan/Div 1 Spec   | BSC                           |                        |
|      |  |       | 0   |  |   |                               |                        |
|      | RUE  | - I   | Prereq  | c) Protected on-site storm sewers  | Provide Plan/Div 1 Spec   | BSC                           |                        |
|      | RUE  |       | l E   | d) Provided swales for hillsides or slopes   | Provide Plan/Div 1 Spec   | BSC                           |                        |
|      | RUE  | S 1   |   | e) Used tiers, blankets, filter socks, berms etc. for slopes >15%  | Provide Plan/Div 1 Spec   | BSC                           |                        |
| T    | RUE  |       |   | f) Prevent air pollution from dust and particulates  | Provide Plan/Div 1 Spec   | BSC                           |                        |
| Т    | RUE  |       |   | g) Construction sites >1 acre meet 2012 EPA Construction General Permit or local equivalent, whichever is more stringent   | Provide Plan/Div 1 Spec   | BSC                           |                        |
| т    | F  | NA    |   | SS-I. No Invasive Plants   | Notes:  | Responsible Party:            | Plan Review Comments:  |
| Т    | RUE  |       | Prereq  | No invasive plants   | Provide schedule/L plans; Add non invasive label or link to resource                                  | Hanover - Brett<br>Montague   |                        |
| Υ    | ?  | N     | Max   |  |   |                               |                        |
| 2    | 0  | 0     | 2   | SS-HI. Heat Island Reduction   | Notes:  | Responsible Party:            | Plan Review Comments:  |
|      |  |       |   | Option 1. Shading  |   | r urty.                       |                        |
|      |  | n/a   | 2   | Locate trees to shade 50% (1pt) or 75% (2pt) of hardscapes and/or  |   |                               |                        |
|      |  |       |   |  | Provide ENERGY STAR roof  |                               |                        |
| 2    |  |       | 2   | Option 2. Nonabsorptive Materials 50 / 75% of hardscapes are light colored, high albedo, or vegetated  | product spec, 100% of roof ES* product  | Cube3                         |                        |
| 0    |  |       |   |  | l .   | Responsible                   | Plan Review Comments:  |
| U    | 2  | 0     | 2   | SS P. Painwater Management   |   | 1100 ponono                   |                        |
|      | 2  | 0     | 3   | SS-R. Rainwater Mangagement  Case 1. Low Impact Development  | Notes:  | Party:                        | Flati Review Comments  |
|      | 2  | 0     | 3*  | SS-R. Rainwater Mangagement  Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated  | Raingarden like at 130?   | 100 I N                       | Figure Review Comments |
| 1.5  | 2  |       | 3*  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  | Raingarden like at 130?   | Party:                        |                        |
| 1.5  |  | 0     |   | Case 1. Low Impact Development   |   | Party:                        |                        |
| 1.5  | 2  |       | 3*  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  | Raingarden like at 130?   | Party:                        |                        |
| 1.5  | 2  |       | 2*  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  | Raingarden like at 130?   | Party:                        |                        |
|      | 2  |       | 3*<br>2*  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control   | Raingarden like at 130?   | Party:                        |                        |
|      | 2  |       | 2*<br>1<br>1  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier   | Raingarden like at 130?   | Party:                        |                        |
|      | 2  |       | 2* 1 1 0.5 0.5  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs   | Raingarden like at 130?   | Party:                        |                        |
|      | 2  |       | 2* 1 0.5 0.5  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide   | Raingarden like at 130?   | Party:                        |                        |
|      | 1.0  |       | 2* 1 1 0.5 0.5 0.5  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials  | Raingarden like at 130?   | Party:                        |                        |
|      | 2  |       | 2* 1 1 0.5 0.5 0.5 0.5  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing)  | Raingarden like at 130?   | Party:                        |                        |
|      | 1.0  |       | 3*  2*  1 1 0.5 0.5 0.5 0.5 0.5                                 | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing) h) Install a registered termite bait system  | Raingarden like at 130?   | Party:                        |                        |
|      | 1.0  |       | 2* 1 1 0.5 0.5 0.5 0.5  | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing) h) Install a registered termite bait system i) >6-inch space between landscape grade and nonmasonry siding   | Raingarden like at 130?   | Party:                        |                        |
| 0.5  | 1.0  |       | 3*  2*  1 1 0.5 0.5 0.5 0.5 0.5                                 | Case 1. Low Impact Development  > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing) h) Install a registered termite bait system i) >6-inch space between landscape grade and nonmasonry siding j) Seal all external cracks, joints, penetrations, edges, and entry  | Raingarden like at 130?   | Responsible                   |                        |
| 0.5  | 1.0  |       | 3*  2*  1 0.5 0.5 0.5 0.5 0.5 0.5                               | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing) h) Install a registered termite bait system i) >6-inch space between landscape grade and nonmasonry siding j) Seal all external cracks, joints, penetrations, edges, and entry points & install rodent-proof screens on openings >0.25 in. k) Design discharge points for rain gutters, condensate lines,  | Raingarden like at 130?  Notes:   | Responsible                   |                        |
| 0.5  | 1.0  |       | 3*  2*  1 1 0.5 0.5 0.5 0.5 0.5 0.5 0.5                         | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing) h) Install a registered termite bait system i) >6-inch space between landscape grade and nonmasonry siding j) Seal all external cracks, joints, penetrations, edges, and entry points & install rodent-proof screens on openings >0.25 in. k) Design discharge points for rain gutters, condensate lines, steam vent lines, etc. >24 in. from foundation l) Design landscape features to provide >18 in. space between | Raingarden like at 130?  Notes:  Add Air Sealing Details to Sections                                  | Responsible Party:  Cube3     |                        |
| 0.5  | 1.0  |       | 3*  2*  1 0.5 0.5 0.5 0.5 0.5 0.5 0.5                           | Case 1. Low Impact Development > 50% (1pt), 65% (2pt), or 80% (3pt) of site is permeable/infiltrated or  SS-PC. Nontoxic Pest Control  a) Install steel mesh barrier termite control b) Install physical termite barrier c) Solid foundation walls d) Install post-tension slabs e) Treat all cellulosic structure with borate termite pesticide f) Use all non-cellulosic structural materials g) Install ports or openings for all slab penetrations (plumbing) h) Install a registered termite bait system i) >6-inch space between landscape grade and nonmasonry siding j) Seal all external cracks, joints, penetrations, edges, and entry points & install rodent-proof screens on openings >0.25 in. k) Design discharge points for rain gutters, condensate lines, steam vent lines, etc. >24 in. from foundation   | Raingarden like at 130?  Notes:  Add Air Sealing Details to Sections                                  | Responsible Party:  Cube3     | Plan Review Comments:  |

| WE:   | Wat  |  | icienc | у   |  | D                     | 1                     |                       |                      |
|-------|------|--|--------|---|--|-----------------------|-----------------------|-----------------------|----------------------|
| T     | F    | NA E   | Prereq | WE-M. Water Metering  | Notes:   | Responsible<br>Party: | Plan Review Comments  |                       |                      |
| TRUE  |      | Water meter or submeter is installed for each unit, or entire building |        |   |  |                       |                       |                       |                      |
| Υ     | ?    | N  | Max    |   |  |                       |                       |                       |                      |
| 5     | 2    | 0 12   |        | 2 0 12  |  | WE-T. Total Water Use | Notes:                | Responsible<br>Party: | Plan Review Comments |
| 5     | 2    |  | 12*    | Use Water Reduction Calculator to show savings for indoor and outdoor uses. Earn 1pt per 5% increment, staring 10% up to 65%    | Provide schedule   |                       |                       |                       |                      |
|       |      |  |        | or  | ı  | In                    |                       |                       |                      |
| 0     | 0    | 0  | 6      | WE-I. Indoor Water Use  | Notes:   | Responsible<br>Party: | Plan Review Comments: |                       |                      |
|       |      | n/a  | 2      | a) Lavatory faucets WaterSense and 1.5gpm (1pt) or 1.0gpm (2pt)   |  | Cube3                 |                       |                       |                      |
|       |      | n/a  | 2      | b) Showerheads WaterSense and 1.75gpm (1pt) or 1.5gpm (2pt)   |  |                       |                       |                       |                      |
|       |      | n/a<br>n/a   | 1      | c) Toilets WaterSense and average 1.1gpf (1pt) d) All washers are ENERGY STAR   |  |                       | -                     |                       |                      |
|       |      | 1110   | Ë      | and/or  |  | Deeneneible           |                       |                       |                      |
| 0     | 0    | 0  | 4      | WE-O. Outdoor Water Use   | Notes:   | Responsible Party:    | Plan Review Comments  |                       |                      |
| 0     | 0    |  | 4      | Reduce turf grass and increase native/adapted plants: T<60%,N>25% (1pt); T<40%,N>50% (2pt); T<20%,N>75% (3pt); T<5%,N>75% (4pt) | Complete Water Reduction Tab Target <5% turf & >75% native/adapted plants; provide plant list and site plan with calcs | Landscape             |                       |                       |                      |
| 5     | 2    | 5  | 12     | SUBTOTAL  |  |                       |                       |                       |                      |
| EA: I | Ener | gy ar  | ıd Atm | osphere   |  |                       |                       |                       |                      |
| т     | F    | NA   |        | EA-P. Minimum Energy Performance (Mid/Highrise)   | Notes:   | Responsible Party:    | Plan Review Comments  |                       |                      |
| 7     | TRUE |  |        | Whole Building Energy Simulation  | Target 15% savings over baseline;  | SWA                   |                       |                       |                      |
|       | TRUE |  |        | a) Achieve 5% energy cost savings over ASHRAE 90.1-2010; and     b) Meet mandatory provisions of ASHRAE 90.1  and               | SWA modeling?  | SWA                   |                       |                       |                      |
|       | N/A  |  |        | Option 1. Cx using ENERGY STAR MFHR T&V Protocols   |  |                       |                       |                       |                      |
|       |      |  | _      | Option 2. Cx using Prescriptive Path (do all of the following)  |  |                       |                       |                       |                      |
| ٦     | rrue |  | Prereq | a) Air sealing, air barrier, compartmentalization details/bid sheets  | Provide air barrier / compartementalization sheet  | Cube3                 |                       |                       |                      |
| 1     | rrue |  |        | b) L-H Thermal Enclosure Inspection Checklist (ESv3r2 Sec. 2,3,5)   | Incorporate items into Arch/MEP plans & specs  | Cube3                 |                       |                       |                      |
| 7     | TRUE |  |        | c) Cx of central systems - meet LEED NC performance testing & ongoing maintenance for central commercial HVAC & DHW             | Incorporate items into MEP HVAC plans & specs  | Cx Agent              |                       |                       |                      |
| 7     | TRUE |  |        | d) Total duct leakage <8cfm25/100sf enclosure   | Incorporate items into MEP HVAC plans & specs  | WBA                   |                       |                       |                      |
| 7     | TRUE |  |        | e) Duct leakg to outside <4cfm25/100sf enclosure (6cfm <1200sf)   | Incorporate items into MEP HVAC  | WBA                   |                       |                       |                      |
| т     | F    | NA   | be     | EA-M. Energy Metering   | Notes:   | Responsible           | Plan Review Comments  |                       |                      |
| - 22  | RUE  |  | Prereq | Install building gas meter and unit-level electric meters/submeters   | whole-building   | Party:<br>WBA         |                       |                       |                      |
| 9000  |      |  |        |   |  | Responsible           |                       |                       |                      |
| Т     | F    | NA   | ed     | EA-ED. Education of Homeowner/Tenant/Building Manager   | Notes:   | Party:                | Plan Review Comments  |                       |                      |
| ٦     | TRUE |  | Prereq | O&M manual, binder, or CD provided to all individuals or organizations responsible for mantenance of home; and                  | Provide manual   | Hanover               |                       |                       |                      |
| 7     | TRUE |  |        | b) Minimum 1hr walkthrough with the occupants and managers  | Provide date/time & attendees  | Hanover               |                       |                       |                      |
| Υ     | ?    | N  | Max    |   |  | In                    | T                     |                       |                      |
| 18.5  | 2    | 0  | 30     | EA-AU. Annual Energy Use (Max 29pt Lowrise, 30pt Midrise)   | Notes:   | Responsible Party:    | Plan Review Comments  |                       |                      |
| 11    | 2    |  | 30*    | Savings from energy model   | 16% current target   | SWA                   |                       |                       |                      |
| 7.5   |      |  | 20     | Home size adjustment  | HSA tab completed  | SWA                   |                       |                       |                      |
| 0     | 1    | 0  | 5      | EA-HW. Efficient Hot Water Distribution System  | Notes:   | Responsible<br>Party: | Plan Review Comments  |                       |                      |
|       |      |  |        | Option 1. Efficient Hot Water Distribution  |  |                       |                       |                       |                      |
|       |      | n/a  | 2      | Path 1. Maximum Allowable Pipe Length Limit pipe length from DHW source to supply (see table)                                   |  |                       |                       |                       |                      |
|       |      | n/a  |        | Path 2. Maximum Allowable Pipe Volume   |  |                       |                       |                       |                      |
|       |      | 400  |        | <64oz DHW stored between source and end use, or   |  | I                     |                       |                       |                      |

|                                       |                                 |        |   |  | 1  | T   |  |  |
|---------------------------------------|---------------------------------|--------|---|--|--|---|--|--|
|                                       |                                 |        |   | Option 2. Performance Test  Case 1. No Circulation Loop or MF w/ Central Circ. Loop  |  |   |  |  |
|                                       |                                 | n/a    | 3   | <0.5gal DHW stored in piping between source and fixture, and   |  |   |  |  |
|                                       |                                 |        |   | or Case 2. Circulation Serves Single Unit, or Heat Trace   |  |   |  |  |
|                                       | n/a                             |        |   | Follow WaterSense test to show <0.25gal stored in branch   |  |   |  |  |
|                                       | and/or Option 3 Pine Insulation |        | Option 3. Pipe Insulation                                   | Ī  |  |   |  |  |
|                                       | 1                               |        | 2   | Install at least R-4 on all DHW piping, including elbows and tees  | Specify DHW R value  |   |  |  |
|                                       |                                 |        |   |  |  | Responsible   |  |  |
| 0                                     | 2                               | 0      | 2*  | EA-UT. Advanced Utility Tracking   | Notes:   | Party:  | Plan Review Comments:  |  |
|                                       |                                 |        |   | Option 1. Electric and Water   |  |   |  |  |
| 0                                     | 1                               |        | 1   | Permanent energy monitor w/ remote data access, or submeter to monitor irrigation systems (min. 1,000 SF irrigated landscape)  | Provide irrigation monitor specs   | Hanover - Brett?  |  |  |
|                                       |                                 |        | $\vdash$  | and/or   |  | -   |  |  |
|                                       |                                 |        |   | Option 2. Third party utility reporting  |  |   |  |  |
| 0                                     |                                 | n/a    |   | Path 1. Whole Building Master Meter Owner shares all applicable utility data w/ USGBC via 3rd party  |  |   |  |  |
|                                       |                                 |        | 1   | or   | 1  |   |  |  |
|                                       | 1                               |        |   | Path 2. Individual Meters  |  |   |  |  |
|                                       |                                 |        |   | >50% of unit owners/occupants share data via 3rd party   |  |   |  |  |
|                                       | П                               |        |   |  |  | Despensible   |  |  |
| 0                                     | 0                               | 0      | 0   | EA-SR. Active Solar-Ready Design (Lowrise only)  | Notes:   | Responsible<br>Party:   | Plan Review Comments:  |  |
|                                       |                                 |        | -   | Option 1. Photovoltaic-Ready Design  |  |   |  |  |
|                                       |                                 | n/a    | 1   | Meet EPA's Solar PV specs for a renewable energy ready home  |  |   |  |  |
|                                       |                                 | - 1    |   | And/or Option 2. Solar Direct Hot Water-Ready Design   |  |   |  |  |
|                                       |                                 | n/a    | 1   | Meet EPA's solar water heating specs for renewable-ready home  |  |   |  |  |
|                                       |                                 |        |   |  |  |   |  |  |
| 0                                     | 0                               | 0      | 0   | EA-C. HVAC Start-up Credentialing (Lowrise only)   | Notes:   | Responsible   | Plan Review Comments:  |  |
|                                       |                                 | n/a    | 1   | All HVAC systems commissioned by a credentialed technician   |  |   |  |  |
| 18.5                                  | 5                               | 14     | 37  | SUBTOTAL   |  |   |  |  |
|                                       |                                 |        |   | - 1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.1.   |  |   |  |  |
| MR:                                   | Mate                            | _      | -   | esources   | Two control of the co | Pegnangible   |  |  |
| T                                     | F                               | NA E   | Prereq  | MR-TW. Certified Tropical Wood   | Notes:   | Responsible Party:  | Plan Review Comments:  |  |
| T                                     | RUE                             |        | 1 5   | All wood in the building is nontropical, reused or reclaimed, or FSC   | Provide letter of confirmation   | Hanover   |  |  |
|                                       | IVOL                            |        |   | The research and banding to Horita opioal, readed of resiamined, of res  | Provide letter of confirmation   | Inanovei  |  |  |
|                                       |                                 |        | _   |  |  |   |  |  |
| Т                                     | F                               | NA     |   | MR-DM. Durability Management (meet all of the following)   | Notes:   | Responsible Party:  | Plan Review Comments:  |  |
| Т                                     | F                               | NA     |   | MR-DM. Durability Management (meet all of the following)   |  | Responsible Party:  | Plan Review Comments: Water Management                           |  |
| Т                                     |                                 | NA     |   |  | Notes:   | Responsible   |  |  |
| T                                     | F                               | NA     |   | MR-DM. Durability Management (meet all of the following)   | Notes: Builder to sign checklist, see  | Responsible Party:  | Water Management   |  |
| <b>T</b>                              | F                               | NA     | Prereq  | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or  | Notes: Builder to sign checklist, see hyperlink  | Responsible Party:  | Water Management   |  |
| <b>T</b>                              | RUE<br>RUE                      | NA     |   | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry  | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  | Responsible Party: Hanover Cube3 Cube3  | Water Management   |  |
| <b>T</b>                              | F<br>RUE<br>RUE                 | NA     |   | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or  | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  | Responsible<br>Party:<br>Hanover<br>Cube3   | Water Management   |  |
| <b>T</b> T                            | RUE<br>RUE                      | NA     |   | a) Meet ESv3 Water Management (meet all of the following)  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor   | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  | Responsible Party: Hanover Cube3 Cube3  | Water Management   |  |
| <b>T</b> T  T  T                      | RUE<br>RUE<br>RUE<br>RUE<br>RUE |        | Prereq  | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space   | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  | Responsible Party: Hanover Cube3 Cube3 Cube3  | Water Management   |  |
| T                                     | RUE<br>RUE<br>RUE<br>RUE<br>RUE | N      | Prereq  | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space     e) Conventional clothes dryers exhausted directly to outside  | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  Rooms   | Responsible Party: Hanover Cube3 Cube3 Cube3  | Water Management<br>System Builder Checklist                     |  |
| <b>T</b> T  T  T                      | RUE<br>RUE<br>RUE<br>RUE<br>RUE |        | Prereq  | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space     e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification   | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  | Responsible Party: Hanover Cube3 Cube3 Cube3 WBA  Responsible Party:  | Water Management   |  |
| T                                     | RUE<br>RUE<br>RUE<br>RUE<br>RUE | N      | Prereq  | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space     e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water  | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  Rooms   | Responsible Party: Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover  | Water Management<br>System Builder Checklist                     |  |
| T T T T T T T T T T T T T T T T T T T | RUE<br>RUE<br>RUE<br>RUE<br>RUE | N      | Max 1   | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space     e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification   | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  Rooms  Notes:   | Responsible Party: Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  | Water Management<br>System Builder Checklist                     |  |
| T T T T T T T T T T T T T T T T T T T | RUE<br>RUE<br>RUE<br>RUE<br>RUE | N      | Max 1   | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space     e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water  | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  Rooms  Notes:   | Responsible Party: Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3 Responsible  | Water Management<br>System Builder Checklist                     |  |
| T T T T T T 1                         | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1   | MR-DM. Durability Management (meet all of the following)      a) Meet ESv3 Water Management System Builder Checklist     b) Nonpaper-faced backer board around shower, or ASTM D3273     c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry     d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space     e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  Rooms  Notes:  Builder to sign, SWA verify  | Responsible Party: Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1                         | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1 5   | MR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)   | Notes:  Builder to sign checklist, see hyperlink  Provide Submittal  Provide Submittals  Provide Submittals Laundry  Rooms  Notes:  Builder to sign, SWA verify  | Responsible Party: Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3 Responsible  | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T T T T T T T T T T T T T T | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1 5 1.5 0.5 0.5                                       | a) Meet ESv3 Water Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273  c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry  d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space  e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi)  a) >50% locally produced Framing  b) >50% locally produced Aggregate for concrete and foundation   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes:   | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover         | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T T T T T T T T T T T T T T | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1 5 1.5 0.5   | a) Meet ESv3 Water Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273  c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry  d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space  e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi)  a) >50% locally produced Framing  b) >50% locally produced Aggregate for concrete and foundation  c) >50% locally produced Gypsum Board / Interior Sheathing   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes:   | Responsible Party:  Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3 Responsible Party:                                    | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T T T T T T T T T T T T T T | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1 5 1.5 0.5 0.5                                       | a) Meet ESv3 Water Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273  c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry  d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space  e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi)  a) >50% locally produced Framing  b) >50% locally produced Aggregate for concrete and foundation   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes:   | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover         | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T T T T T T T T T T T T T T | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1 5 1.5 0.5 0.5 0.5                                   | mR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes:   | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover         | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T T T T T T T T T T T T T T | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 4* 2 1                                | mr.Dm. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry  d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  mr.Dv. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  mr.EP. Environmentally Preferable Products (LR 4pt/mr 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes: Provide product specs/origin Provide product specs/origin   | Responsible Party:  Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover           | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE RUE RUE         | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | MR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry  d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP c) 90% Insulation EPP (exclude HVAC and pipe insulation)   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes: Provide product specs/origin Provide product specs/origin   | Responsible Party:  Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover           | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | mR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes: Provide product specs/origin Provide product specs/origin   | Responsible Party:  Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover           | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1                       | MR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP e) 90% Framing EPP  | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes: Provide product specs/origin Provide product specs/origin   | Responsible Party:  Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover           | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 | mR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes:  Builder to sign, SWA verify  Notes:  Provide product specs/origin Provide product specs/origin Provide Submittals Provide Submittals Provide Submittals  | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover         | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1 1                     | mR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist  b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP e) 90% Framing EPP f) 90% Drywall EPP g) 90% Concrete contains 30%+ flyash/slag as cement replacement & 50% RC aggregate; or 90% RC aggregate   | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes: Builder to sign, SWA verify  Notes: Provide product specs/origin Provide product specs/origin   | Responsible Party:  Hanover Cube3 Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover           | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1 1                     | mR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering tePP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP e) 90% Framing EPP f) 90% Drywall EPP g) 90% Concrete contains 30%+ flyash/slag as cement replacement & 50% RC aggregate; or 90% RC aggregate h) 90% Roofing EPP  | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes:  Builder to sign, SWA verify  Notes:  Provide product specs/origin Provide product specs/origin Provide Submittals Provide Submittals Provide Submittals  | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover         | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1 1 1 1 1 1 1                         | MR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering EPP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP e) 90% Framing EPP f) 90% Drywall EPP g) 90% Concrete contains 30%+ flyash/slag as cement replacement & 50% RC aggregate; or 90% RC aggregate h) 90% Roofing EPP i) 90% Siding EPP | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes:  Builder to sign, SWA verify  Notes:  Provide product specs/origin Provide product specs/origin Provide Submittals Provide Submittals Provide Submittals  | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover Hanover | Water Management System Builder Checklist  Plan Review Comments: |  |
| T T T T T T 1 1 2.0 0.5 0.5           | RUE RUE RUE RUE 3.0             | N<br>0 | Max 1 1 5 1.5 0.5 0.5 1.1 1 1 1 1 1 1 1                     | mR-DM. Durability Management (meet all of the following)  a) Meet ESv3 Water Management System Builder Checklist b) Nonpaper-faced backer board around shower, or ASTM D3273 c) Water-resistant flooring in kitchen, baths, laundry, spa areas or within 3' of exterior entry d) Drain pan+drain or automatic shut-off or floor drain+sloped floor for tank water heaters & clothes washers in/over living space e) Conventional clothes dryers exhausted directly to outside  MR-DV. Durability Management Verification  Green rater verifies all measures in ENERGY STAR Homes v3 water management system builder checklist via field inspection/photos  MR-EP. Environmentally Preferable Products (LR 4pt/MR 5pt)  Option 1. Local (extraction + processing within 100mi) a) >50% locally produced Framing b) >50% locally produced Aggregate for concrete and foundation c) >50% locally produced Gypsum Board / Interior Sheathing and/or  Option 2. Environmentally Preferable Products a) No Floor Covering (base only, i.e. sealed concrete) b) 90% Floor Covering tePP c) 90% Insulation EPP (exclude HVAC and pipe insulation) d) 90% Sheathing EPP e) 90% Framing EPP f) 90% Drywall EPP g) 90% Concrete contains 30%+ flyash/slag as cement replacement & 50% RC aggregate; or 90% RC aggregate h) 90% Roofing EPP  | Notes:  Builder to sign checklist, see hyperlink Provide Submittal Provide Submittals Provide Submittals Laundry Rooms  Notes:  Builder to sign, SWA verify  Notes:  Provide product specs/origin Provide product specs/origin Provide Submittals Provide Submittals Provide Submittals  | Responsible Party:  Hanover Cube3 Cube3 WBA  Responsible Party: Hanover Cube3  Responsible Party: Hanover Hanover Hanover Hanover         | Water Management System Builder Checklist  Plan Review Comments: |  |

|     |      |          |          |   |   | Responsible        |                        |
|-----|------|----------|----------|---|---|--------------------|------------------------|
| 0.5 | 0.5  | 0        | 3        | MR-CW. Construction Waste Management  | Notes:  | Party:             | Plan Review Comments   |
| 0.5 | 0.5  |          | 3*       | Reduce total construction waste. See Rating System for points.  | Provide WMP & final calcs                       | Hanover            |                        |
| 0.0 | 0.0  | 0        | 0        | Material Efficient Framing (Lowrise only)   | Notes:  | Responsible Party: | Plan Review Comments   |
|     |      | n/a      |          | Select one of the following for exterior & common walls:  a) No more than one horizontal 2x top plate on walls                                |   |                    |                        |
|     |      | n/a      | 1        | b) Window and door headers were placed in the rim joist   |   |                    |                        |
|     |      | n/a      |          | c) Raised single ply headers <2" thick in2x4 / <4" in 2x6 wall  |   |                    |                        |
|     |      | n/a      |          | d) Structural insulated panels for walls  |   |                    |                        |
|     |      | n/a      |          | Select at least 2 of the following for interior & exterior walls:   |   |                    |                        |
|     |      |          | 0.5      | e) Headers were sized for loads.  f) Ladder blocking or drywall clips used.   |   |                    |                        |
|     |      | n/a      | 0.5      | Lauder blocking of drywaii crips dised.   |   |                    |                        |
|     |      | n/a      |          | g) Two-stud corners or California corners were used.  |   |                    |                        |
|     |      | n/a      | 0.5      | Select all that apply (90%+ of component)  h) Interior wall study were spaced greater than 16 inches o c                                      |   |                    |                        |
|     |      | n/a      | 0.5      | i) Floor joists spaced greater than 16 inches o.c.  |   |                    |                        |
|     |      | n/a      | 0.5      | j) Roof rafers spaced greater than 16 inches o.c.   |   |                    |                        |
| 3.5 | 3.5  | 2.0      | 9        | SUBTOTAL  |   | l:                 | 1                      |
|     |      |          |          | mental Quality  |   |                    |                        |
| т   | F    | NA       |          | EQ-V. Ventilation (meet all of the following)   | Notes:  | Responsible        | Plan Review Comment    |
|     |      |          | - B      | Local Exhaust   | Provide 62.2 calcs for apartments,              | Party:             |                        |
|     | RUE  |          | Prereq   | a) Meet ASHRAE 62.2-2010 Sections 5 & 7 in baths & kitchens   | 62.1 common                                     | WBA                |                        |
| _   | RUE  | -        | -        | b) Exhaust directly to the outdoors c) Bath fans ENERGY STAR (or HRV/ERV is used)   |   | WBA<br>WBA         | -                      |
| - 1 | NUL  | _ '      |          |   |   | IVVBA              |                        |
| Т   | RUE  |          |          | Whole Unit Mechanical Ventilation a) Project meets ASHRAE 62.2-2010 sections 4 and 7  | Provide 62.2 calcs for apartments, 62.1         | WBA                |                        |
|     | RUE  |          | Prereq   | b) Do not rely on transfer air from adjacent spaces incl. corridors   |   | WBA                |                        |
|     | RUE  | -        | <u> </u> | c) Continuous fans <1.0 sone (Section 7.2.1) or remote mounted d) Locate ventilation air inlets 10' from contamination sources,               | Provide system plan design,                     | WBA                | -                      |
| 1   | RUE  |          |          | protected with mesh <0.5in, and clear of obstruction (Sect. 6.8)  | product specs, vent calcs                       | WBA                |                        |
| ī   | RUE  |          | 6        | Non-Unit Spaces   | Provide v4 Min IAQ Perf Calcs for               | WBA                | Minimum IAQ            |
|     |      |          | Prereq   | a) Meet ASHRAE 62.1-2010 sections 4 and 7   | GBCI review                                     | 1000-1000          | Performance Calculator |
|     | N/A  |          | _        | b) Projects in nonattainment areas for PM2.5 or ozone, see reqmt's  |   |                    |                        |
| т   | F    | NA       |          | EQ-CV. Combustion Venting (meet all of the following)   | Notes:  | Responsible Party: | Plan Review Commen     |
| Т   | RUE  | $\neg$   |          | b) Vent all combustion appliances (except ovens and range)  | NA  | WBA                |                        |
| т   | RUE  |          |          | c) CO monitor on each floor of each unit, hard-wired w/ battery   | Provide plan w/ locations,                      | WBA                |                        |
|     | NOL  |          | Prereq   | backup or 10-yr battery model   | system/product specs, SWA to<br>verify in field | WBA                |                        |
|     | N/A  |          | a P      | d) Fireplaces & stoves have closing doors or solid glass enclosure     e) Fireplaces and stoves are closed combustion or power vented,        | Clubhouse fireplance will comply                | WBA                |                        |
|     | N/A  |          |          | or pass BPI/RESNET cobustion safety test to ensure  | Clubhouse fireplance will comply                | WBA                |                        |
| Т   | RUE  |          |          | depressurization of combustion appliance zone <5Pa f) Combustion space and water heating eqiupment is closed                                  | Clubhouse fireplance will comply                | WBA                | 1                      |
| - 8 | NOL. | _        | _        | combustion, power vented, or remote located   | Clubriouse irreplance will comply               |                    |                        |
| т   | F    | NA       |          | EQ-G. Garage Pollutant Prevention (meet all of the following)   | Notes:  | Responsible Party: | Plan Review Commen     |
| Т   | RUE  |          | Prereq   | All air handling equipement serving conditioned space located outside fire-rated envelope of the garage                                       | Provide schedule/plan                           | WBA                |                        |
| Т   | RUE  |          | Pre      | <ul> <li>Tightly seal shared surfaces between the garage and<br/>conditioned spaces, bases of walls, including interstitial space,</li> </ul> | Provide schedule/plan                           | WBA                |                        |
| Т   | RUE  |          |          | penetrations, and weather-stripped doors c) Install CO monitors in conditioned spaces with access to garage                                   | Provide schedule/plan                           | WBA                |                        |
| т   | F    | NA       |          | EQ-R. Radon-Resistant Construction  | Notes:  | Responsible        | Plan Review Commen     |
|     | Dire | $\dashv$ |          | Case 1. New Construction in EPA Radon Zone 1 (meet all below:)  | Devide and a selection                          | Party:             |                        |
| - 1 | RUE  |          | *5       | a) Capillary break per Indoor airPLUS   | Provide radon mitigation plans                  | Cube3/WBA          | _                      |
| T   | RUE  |          | Prereq*  | b) Electric outlet near vent piping in attic for future fan install   | Provide radon mitigation plans                  | Cube3/WBA          |                        |
|     | DITE | - 1      | 200      | c) Gas-tight vent pipe from below capillary break to 12" above roof   | Provide radon mitigation plans                  | Cube3/WBA          | I                      |
| Т   | RUE  |          |          | c) das-tigrit verit pipe from below capillary break to 12 above roof  | 1 Tovide radori miligation plans                | Cubes/WDA          |                        |

| N   | I/A     |          | Case 2. Building Renovation in EPA Radon Zone 1 Active ventilation system installed if radon test results > 4 pCi/L   |   |                    |                       |
|-----|---------|----------|---|---|--------------------|-----------------------|
| т   | F NA    |          | EQ-F. Air Filtering (meet all of the following)   | Notes:  | Responsible        | Plan Review Comments: |
| TF  | RUE     | Prereq   | a) MERV 8 or higher filters on recirculating forced air systems   | Provide filter specs, SWA to verify                   | Party:<br>WBA      |                       |
| TF  | RUE     | <u>~</u> | b) MERV 6 or higher filters on mechanically supplied outdoor air  | in field Provide filter specs, SWA to verify in field | WBA                |                       |
| т   | F NA    | -        | EQ-TS. Environmental Tobacco Smoke  | Notes:  | Responsible Party: | Plan Review Comments: |
| TR  | RUE     | Prereq   | Prohibit smoking in common areas; locate any outdoor designated smoking areas >25ft from entries, outdoor air intakes, and operable windows; install signs to show restrictions | Provide smoking policy in manual, signage             | Hanover            |                       |
| т   | F NA    |          | EQ-C. Compartmentalization (meet all of the following)  | Notes:  | Responsible Party: | Plan Review Comments: |
|     | RUE     | Prereq   | a) Seal each unit including penetrations through walls, ceilings, floors, & vertical chases adjacent to units     b) Weather-strip all unit doors leading to common hallways    | All apartments compartmentalized, air sealing details | Cube3/WBA          |                       |
| TR  | RUE     | _        | Weather-strip all exerior doors and operable windows     Dwelling unit leakage with blower door test <0.23cfm50 per     SF enclosure (0.30 if average unit size <1200 SF)       | Add requirement to specs                              | Cube3              |                       |
| Υ   | ? N     | Max      |   |   |                    |                       |
| 1   | 0 0     | 3        | EQ-EV. Enhanced Ventilation   | Notes:  | Responsible Party: | Plan Review Comments: |
| 1   | n/a     | 1        | Option 1. Enhanced Local Exhaust Bathroom exhaust fan control in every bathroom   | Confirm bathroom exhaust strategy                     | WBA                |                       |
| 0   | n/a     | 2        | Option 2. Enhanced Whole-House Ventilation Design & install balanced whole-house ventilation system to meet ASHRAE 62.2-2010; within 100-110% of ASHRAE flows                   |   |                    |                       |
| 0.5 | 0.5 0   | 2*       | EQ-CC. Contaminant Control  | Notes:  | Responsible Party: | Plan Review Comments: |
| 0.5 |         | 0.5      | Option 1. Walk-Off Mats Permanent walk-off mats >4ft (dwelling unit) or 10ft (common entry)   | Provide in flooring plans                             | Cube3              |                       |
|     | n/a     | 0.5      | Option 2. Shoe Removal Shoe removal and storage spaced near primary entryway  |   |                    |                       |
|     | 0.5 n/a | 0.5      | Option 3. Preoccupancy Flush Protect ducts; Flush >48hrs after construction but before occupancy and/or   | Provide strategy and dates/times                      | Hanover            |                       |
|     | n/a     | 1        | Option 4. Air Testing Test for IAQ after construction but before occupancy  |   |                    |                       |
| 2   | 1 0     | 3        | EQ-B. Balancing of Heating & Cooling Distribution Systems   | Notes:  | Responsible Party: | Plan Review Comments: |
|     | n/a     | 3        | Case 1. Forced-Air System Option 1. Multiple Zones  |   |                    |                       |
| 1   |         |          | a) 2+ zones w/ independent thermostat controls; or     b) Automatic for SF homes <800 SF & MF avg unit <1200 SF and/or  | Avg. unit <1200sf                                     |                    |                       |
| 1   |         | 1        | Option 2. Supply Air-Flow Testing Supply air flow tested within 80-120% of Manual J calc  | Hire TAB contractor/add to specs                      | WBA                |                       |
|     | 1       | 1        | Option 3. Pressure Balancing Pressure differential between bedroom and rest of home <3 Pa   |   |                    |                       |
|     |         | 3        | Case 2. Radiative Systems   |   |                    |                       |
|     | n/a     | 1        | Option 1. Multiple Zones  a) 2+ zones w/ independent thermostat controlling separate loop/pump per zone (radiators see Option 2); or  |   |                    |                       |
|     | n/a     |          | b) Automatic for SF homes <800 SF & MF avg unit <1200 SF  |   |                    |                       |
|     | n/a     | 2        | and/or Option 2. Room-by-room Controls  |   |                    |                       |
| 0   | 0 0     | 3        | EQ-EC. Enhanced Compartmentalization (LR 1pt / MR 3pt)  | Notes:  | Responsible Party: | Plan Review Comments: |
|     | n/a     | 3        | Dwelling unit leakage with blower door test <0.15 CFM50/sf  | TBD pending final testing                             | SWA                |                       |
| 1   | 0 0     | 2        | EQ-ECV. Combustion Venting  | Notes:  | Responsible Party: | Plan Review Comments: |
| 0   | n/a     | 2        | Option 1. No Fireplace or Wood Stove  | 1   | i.                 |                       |
|     | n/a     |          | a) EPA certified wood/pellet-burning stove with direct/power vent   |   |                    |                       |

|   |                         | n/a                     | 1                      | b) EPA qualified wood burning fireplace with direct/power vent c) Natural gas/propane/alcohol stove listed by approved safety  |  |   |  |
|---|-------------------------|-------------------------|------------------------|--|--|---|--|
| 1                                       |                         | n/a                     |                        | testing facility, with power/direct vent, permanent fixed glass<br>front or gasketed door, and electronic pilot  | Clubhouse will comply  |   |  |
| 1                                       | 0                       | 0                       | 1                      | EQ-EG. Enhanced Garage Pollutant Protection (LR 2pt/MR 1pt)  | Notes:   | Responsible<br>Party:                               | Plan Review Comments:  |
| 1                                       |                         |                         | 1                      | Option 1. Exhaust Fan in Garage Meet ASHRAE 62.1-2010 (or 75 CFM & ENERGY STAR in SF) and use appropriate controls; test pressure differential (MF only)   | Provide MEP Garage design  | WBA   |  |
| 0                                       |                         | n/a                     | 1                      | Option 2. Detached Garage or No Garage or Carport  |  |   |  |
| 1.5                                     | 1.5                     | 0                       | 3                      | EQ-EP. Low-Emitting Products   | Notes:   | Responsible Party:                                  | Plan Review Comments:  |
| 0.5                                     |                         |                         | 0.5                    | a) Site-applied interior paints and coatings meet CA Section 01350   | Provide Submittals   | Cube3   |  |
| 0.5                                     | 0.0                     |                         | 0.5                    | b) Flooring is Floorscore, CRI Green Label Plus, or CA 01350   | Provide Submittals   | Cube3   |  |
| 0.0                                     | 0.5                     |                         | 0.5                    | c) Insulation is Greenguard Gold, CHPS, or meets CA 01350  | Provide Submittals   | Cube3   |  |
| 0.5                                     |                         |                         | 0.4                    |  | Provide Submittals   | Cube3   |  |
| 0                                       | 1                       |                         | 1                      | e) Composite wood products meets CARB ultra-low-emitting formaldehyde (ULEF) resins or no-added formaldehyde resins  | Provide Submittals   | Cube3   |  |
| 1                                       | 0                       | 0                       | 1                      | EQ-NS. No Environmental Tobacco Smoke (Midrise only)   | Notes:   | Responsible Party:                                  | Plan Review Comments:  |
| 1                                       |                         |                         | 1                      | Prohibit smoking throughout the building, including within units   | Provide smoking policy in manual, signage  | Hanover   |  |
| 8.0                                     | 3.0                     | 7.0                     | 18                     | SUBTOTAL   |  |   | *  |
| IN: Ir                                  | nov                     | /atio                   | n                      |  |  |   |  |
| Т                                       | F                       | NA                      | le l                   | IN-PR. Preliminary Rating  | Notes:   | Responsible Party:                                  | Plan Review Comments:  |
| Т                                       | RUE                     | •                       | Fir                    | Conduct a preliminary LEED meeting and create an action plan, with the participation of the principal members of the verification and project teams  | 3/16/18 Kickoff; 4/13/18 pt.2 follow<br>up   | SWA   |  |
| Y                                       | ?                       | N                       | Ma                     | (  |  |   |  |
|   |                         |                         |                        |  |  |   |  |
| 3.0                                     | 0.0                     | 0                       | 5                      | IN-IN. Innovation  | Notes:   | Responsible<br>Party:                               | Plan Review Comments:  |
| 3.0                                     | 0.0                     | 0<br>n/a                | 1                      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval  | Notes:   | Market de production and the second                 | Plan Review Comments:  Design for Accessibility                              |
| 3.0                                     | 0.0                     | 100                     |                        | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library   | Notes:   | Market de production and the second                 | Part The Install Control   |
|   | 0.0                     | n/a<br>n/a              | 1                      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit  | ID Trades Training LT Access to Transit LT Community Resources (20)  | Market de production and the second                 | Design for Accessibility  Design for Active                                  |
|   |                         | n/a<br>n/a              | 1                      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance  | ID Trades Training<br>LT Access to Transit   | Party:  | Design for Accessibility  Design for Active                                  |
|   |                         | n/a<br>n/a              | 1                      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance  | ID Trades Training LT Access to Transit LT Community Resources (20)  | Party:  | Design for Accessibility  Design for Active                                  |
| 3.0                                     | 0.0                     | n/a                     | 3                      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities   | ID Trades Training<br>LT Access to Transit<br>LT Community Resources (20)  | SWA Responsible                                     | Design for Accessibility  Design for Active Occupants                        |
| 3.0                                     | 0.0                     | n/a                     | 3                      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes: Provide project team member  | SWA  Responsible Party:                             | Design for Accessibility  Design for Active Occupants                        |
| 3.0<br>1<br>1<br>4.0<br>RP: I           | 0.0<br>0<br>0.0<br>Reg  | n/a n/a 0 2.0           | 1 3 1 1 1 6 Prior      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional LEED AP serves as principal participant of the project team by SD  SUBTOTAL  | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes: Provide project team member  | SWA  Responsible Party:                             | Design for Accessibility  Design for Active Occupants                        |
| 3.0<br>1<br>1<br>4.0<br>RP: I           | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional     | 1 1 3 1 1 1 6 Prior Ma | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  LEED AP serves as principal participant of the project team by SD  SUBTOTAL   | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes:  Provide project team member certification   | SWA  Responsible Party:  Design Team                | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |
| 3.0<br>1<br>1<br>4.0<br>RP: I           | 0.0<br>0<br>0.0<br>Reg  | n/a n/a 0 2.0           | 1 3 1 1 1 6 Prior      | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional LEED AP serves as principal participant of the project team by SD  SUBTOTAL  | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes:  Provide project team member certification   | SWA  Responsible Party:                             | Design for Accessibility  Design for Active Occupants                        |
| 3.0<br>1<br>1<br>4.0<br>RP: I           | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional     | 1 1 3 1 1 1 6 Prior Ma | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  LEED AP serves as principal participant of the project team by SD  SUBTOTAL   | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes: Provide project team member certification  Notes: Annual Energy Use (need min 15pts)   | Responsible Party:  Design Team  Responsible Party: | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |
| 3.0<br>1<br>1<br>4.0<br>RP: I           | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional     | 1 1 3 1 1 1 6 Prior Ma | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  LEED AP serves as principal participant of the project team by SD  SUBTOTAL   | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes: Provide project team member certification  Notes: Annual Energy Use (need min  | Responsible Party:  Design Team  Responsible Party: | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |
| 3.0<br>1<br>1<br>4.0<br>RP: I<br>Y      | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional     | 1 1 1 1 6 Prior Ma 4   | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  LEED AP serves as principal participant of the project team by SD  SUBTOTAL  ty  RP. Regional Priority  | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes: Provide project team member certification  Notes: Annual Energy Use (need min 15pts) Balancing Heating & Cooling (need   | Responsible Party:  Design Team  Responsible Party: | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |
| 3.0<br>1<br>1<br>4.0<br>RP: I<br>Y      | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional     | 1 1 1 1 6 Prior Ma 4   | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  LEED AP serves as principal participant of the project team by SD  SUBTOTAL  ty  RP. Regional Priority  | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes:  Provide project team member certification  Notes:  Annual Energy Use (need min 15pts)  Balancing Heating & Cooling (need 3pte)  | Responsible Party:  Design Team  Responsible Party: | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |
| 3.0<br>1<br>1<br>4.0<br>RP: I<br>Y      | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional     | 1 1 1 1 6 Prior Ma 4   | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional  LEED AP serves as principal participant of the project team by SD  SUBTOTAL  ty  RP. Regional Priority  | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes:  Provide project team member certification  Notes:  Annual Energy Use (need min 15pts)  Balancing Heating & Cooling (need 3pts)  Access to Transit (need 2pts)   | Responsible Party:  Design Team  Responsible Party: | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |
| 3.0<br>1<br>1<br>4.0<br>RP: 1<br>Y<br>3 | 0.0<br>0<br>0.0<br>Regi | n/a n/a 0 2.0 ional N 0 | 1 1 3 Prior Ma 4       | Option 1. Innovation Choose from Innovation Catalog or submit idea for approval and/or Option 2. Pilot Credit Choose from Pilot Credit Library and/or Option 3. Exemplary Performance See items with (*) by Max Points for Exemplary opportunities  IN-AP. LEED Accredited Professional LEED AP serves as principal participant of the project team by SD SUBTOTAL  ty  RP. Regional Priority  Earn 1pt bonus point each for credits identified as local priorities  Certified: 40-49 points, Silver: 50-59 points, Gold: 60-79 points | ID Trades Training LT Access to Transit LT Community Resources (20)  Notes:  Provide project team member certification  Notes:  Annual Energy Use (need min 15pts)  Balancing Heating & Cooling (need 3pte)  Access to Transit (need 2pts)  Heat Island Reduction (need 2pt)  Non Toxic Pest (need 2pt)? | Responsible Party:  Design Team  Responsible Party: | Design for Accessibility  Design for Active Occupants  Plan Review Comments: |

MAHESH RAMANUJAN PRESIDENT & CEO, U.S. GREEN BUILDING COUNCIL PRESIDENT & CEO, GREEN BUSINESS CERTIFICATION INC. halod Commigon green building practices and principles needed to support GREEN BUSINESS CERTIFICATION INC. CERTIFIES THAT by demonstrating the knowledge and understanding of LEED AP® Building Design + Lauren Hildebrand the use of the LEED green building program. HAS ATTAINED THE DESIGNATION OF Construction 10061260-AP-BD+C BD+C 03 SEP 2009 01 SEP 2019 VALID THROUGH

## LEED FOR HOMES GREEN RATER

## Lauren Hildebrand

S ATTAINED THE DESIGNATION (

# LEED® FOR HOMES GREEN RATER

by demonstrating the knowledge and understanding of green building practices and principles needed to support the use of the LEED  $^{^{\circ}}$  green building program.



MAHESH RAMANUJAN PRESIDENT & CEO, U.S. GREEN BUILDING COUNCIL PRESIDENT & CEO, GREEN BUSINESS CERTIFICATION INC.

VALID THROUGH

06 MAY 2020

07 MAY 2013

10061260-GR

CREDENTIAL ID

June 5, 2018



Tom Denney Vice President The Hanover Company 2 Seaport Lane – 11<sup>th</sup> Floor Boston, MA 02210

Re: Acoustical Narrative 50 CambridgePark Drive Cambridge, Massachusetts

## ACOUSTICAL NARRATIVE

This acoustical narrative addresses the acoustical design elements of the proposed 50 CambridgePark Drive project for The Hanover Company in Cambridge, Massachusetts. The project site needs to comply with the City of Cambridge noise regulations as well as the Massachusetts state regulation.

## APPLICABLE NOISE REGULATIONS

## Massachusetts

The Massachusetts Department of Environmental Noise Policy, DEP 310 CMR 7.10, states that:

The DEP has established a Noise Level Policy for implementing this regulation. The policy specifies that the ambient sound level, measured at the property line of the facility or at the nearest inhabited buildings, shall not be increased by more than 10 decibels weighted for the "A" scale [dB(A)] due to the sound from the facility during its operating hours.

The guideline further states that the facility shall not produce a pure-tone condition at the property line (or at the nearest inhabited buildings). A pure-tone exists if the sound pressure level, at any given octave band center frequency, exceeds the levels of the two adjacent octave bands by three (3) or more decibels.

For this project, we assume that the existing background sound levels are high enough in the project area that meeting the City of Cambridge Noise Regulation will be the more stringent requirement.

## City of Cambridge Noise Regulation

The City of Cambridge has separate sound level limits based on zoning type and the time of day. There are both Commercial and Residential Zones adjacent to this project. Therefore, the noise generated by the equipment of this project will be designed to meet the more stringent Residential

SLR International Corporation 6001 Savoy Drive, Suite 215, Houston, TX 77036-3322
T: (713) 789-9400 F: (713) 789-5493 www.slrconsulting.com
Offices throughout USA, UK, Ireland, Canada, Australia, Namibia, and South Africa

Zone noise requirement as noted in the following table which shows the maximum allowable octave band sound pressure levels as given in the City of Cambridge Noise Regulations.

| Octave Band Center<br>Frequency of<br>Measurement (Hz) | Residential Area<br>(Daytime) dB | Residential Area<br>(Nighttime) dB | Commercial/Business<br>(All Times) dB |  |
|--|----------------------------------|------------------------------------|---------------------------------------|--|
| 31.5   | 76                               | 68                                 | 79                                    |  |
| 63   | 75                               | 67                                 | 78                                    |  |
| 125  | 69                               | 61                                 | 73                                    |  |
| 250  | 62                               | 52                                 | 68                                    |  |
| 500  | 56                               | 46                                 | 62                                    |  |
| 1000   | 50                               | 40                                 | 56<br>51<br>47                        |  |
| 2000   | 45                               | 33                                 |                                       |  |
| 4000   | 40                               | 28                                 |                                       |  |
| 8000   | 38                               | 26                                 | 44                                    |  |
| Single Number<br>Equivalent                            | 60 dBA                           | 50 dBA                             | 65 dBA                                |  |

City of Cambridge Maximum Allowable Octave Band Sound Pressure Levels

Daytime is defined by the City of Cambridge as the period between 7 AM and 6 PM except Sundays and holidays.

## PRELIMINARY PROJECT EQUIPMENT ANALYSIS

Our noise analysis for this project is based upon the typical mechanical equipment used on similar Hanover project including nearby projects: 88 CambridgePark Drive, 130 CambridgePark Drive, and 160 CambridgePark Drive. The following is a list of the type of equipment that are anticipated and the sound attenuation measures that will be incorporated into the design.

- Rooftop condensing units (similar to Carrier 24ABB318 used on 88 CambridgePark Drive project): One condensing unit per apartment unit, located on the roof toward the center of the corridors and away from the perimeter.
- Rooftop Air Handling Unit (similar to Carrier 48HCTA06, 48HCED08 used on 88 CambridgePark Drive project): Three units located on the roof, will be positioned to minimize the visual site lines to adjacent properties and to allow for sound barrier attenuation from the roof.
- Garage exhaust fan facing east on Levels 1-2 (similar to Greenheck SBE-2L42-50 used on 88 CambridgePark Drive project): sound attenuators will be incorporated into the design to meet the noise requirements.
- 200 KW emergency generator located on roof (similar to Kohler 200RZX with sound enclosure and muffler): these units will have a sound enclosure to meet 69 dBA sound level at 23 feet. In addition, the generator location will be chosen to maximize the sound barrier attenuation properties of the roof.



## SOUND LEVEL PREDICTIONS TO ADJACENT PROPERTY RECEIVERS

Based upon our calculations, the predicted sound levels generated from the 50 CambridgePark Drive property will be as follows at the nearest noise sensitive properties:

| Address of<br>Receiver     | Distance from<br>50<br>Cambridgepark | Zoning      | Daytime<br>Sound Level<br>WITH<br>Emergency<br>Generator | Nighttime<br>Sound Level<br>WITHOUT<br>Emergency<br>Generator |
|----------------------------|--------------------------------------|-------------|--|---|
| 30 CambridgePark<br>Drive  | 80 feet                              | Residential | 47 dBA   | 45 dBA  |
| 35 CambridgePark<br>Drive  | 95 feet                              | Commercial  | 51 dBA   | 44 dBA  |
| 88 CambridgePark<br>Drive  | 60 feet                              | Residential | 53 dBA   | 45 dBA  |
| 100 CambridgePark<br>Drive | 87 feet                              | Commercial  | 55 dBA   | 45 dBA  |
| 130 CambridgePark<br>Drive | 90 feet                              | Residential | 53 dBA   | 44 dBA  |

## **Tone Evaluation**

Based upon the equipment sound data and the predicted sound levels to the closest receivers, we do not anticipate any tonal sounds as defined by the State of Massachusetts.

## CONCLUSION

Based upon our analysis, the noise from the mechanical noise sources identified for this project will meet the City of Cambridge Noise Regulations

This concludes this Technical Memorandum. Please call if you have any questions or comments.

Sincerely,

**SLR International Corporation** 

Nicholas A Block, P.E., LEED AP BD+C

Associate Engineer

OCL/NAB/nab

SLR Draft Technical Memo - The Hanover Company - 50 Cambridgepark - Acoustical Narrative 6-5-2018.docx



## Community Engagement Meeting April 24, 2018: Attendee Questions and Development Team Responses

## **Design and Resiliency**

- 1. Q: Can more green area or gathering spaces be added to the Project Site, especially around the retail frontage?
- A: A primary design objective is to bring retail frontage directly to Cambridgepark Drive. We hope this spurs additional retail at other parcels on the street, where related greenspace or gathering areas will be more appropriate. The Project does include greenspace and a focal point for gathering at the rear of the Project Site facing the 88 CPD and 100 CPD buildings.
- 2. Q: How much of the Project Site will permeable and impermeable?
- A: The Project is currently 2% permeable. The Project will increase this amount to 12% permeable.
- 3. Q: Is the Developer aware of the petition to amend the zoning ordinance relative to climate change preparedness?
- A: Yes. We believe that our Project is responsive to many of the concerns raised in the proposed amendment.
- 4. Q: In courtyards, are we proposing additional landscape or stormwater retention?
- A: We are investigating that, and we continue to investigate how we can improve those aspects of the Project across the Project Site throughout the site.

## Traffic

- 5. Q: Is the Rindge Avenue / Sherman Street intersection within the scope of intersections studied?
- A: No, this intersection is not within the scope of the required City traffic study.
- 6. Q: Is the developer advocating for the City to re-align Rindge Avenue and Cambridgepark Drive to create a four-way intersection at Alewife Book Parkway?
- A: Others are in a better position to advocate for that kind of action by the City, but we would support such a change if it helped to mitigate traffic congestion in the Triangle.
- 7. Q: How do we calculate project vehicular trips generated?
- A: The City requires a specific methodology and we adhere to that. This requires gathering of actual traffic data from neighboring projects.

- 8. Q: How does actual data gathered compare to what was projected for these neighboring projects? For example, for 160 Cambridgepark Drive?
- A: We have not studied that but we can.

## **Operations**

- 9. Q: We understand that the shared driveway along the western boundary of the project site is a private road. Can you describe how it will be operated and maintained?
- A: The shared driveway will look and function like a City street, and will even include on-street parallel parking spaces. Because it is a private road, it will be maintained by the Developer and not the City.
- 10. Q: Can you describe how loading operations will function at the Project?
- A: The Project will have one loading dock sized to accommodate the moving vans typical of apartments of the size proposed in the Project.
- 11. Q: Will the Project have 24/7 property manager on site?
- A: Yes.

## **Environment**

- 12. Q: Can you elaborate on the Project's noise impacts?
- A: Noise impacts will be minimal. Rooftop equipment will be screened and not audible at street level. We will comply with City guidelines with respect to noise.
- 13. Q: Do you have a plan to deal with the corrosive quality of Cambridge water?
- A: Yes, it is being addressed.
- 14. Q: What environmental investigations have been performed? Can the Developer share those reports with the public?
- A: As with other Hanover projects in the Triangle, we performed Phase I and Phase II studies. These indicated that the Project Site contains urban fill typical of sites in this area.
- 15. Q: Can we share our environmental report?
- A: It is typical to consider environmental studies and other project diligence reports as private. The Developer will continue to answer any environmental questions raised throughout the public process for the Project.

## Other

- 16. Q: What public schools will Project residents attend and how will they get there?
- A: As with all families in Cambridge who choose to attend Cambridge public schools, families living at the Project will participate in the City's Controlled Choice school lottery. The website of the Cambridge Public School District ("CPSD") indicates that both the Peabody School and the Graham & Parks School are proximity schools for the Project Site. The CPSD school bus network will be available to families residing at the Project.
- 17. Q: What efforts did the Developer make to notify residents of the Community Engagement Meeting?
- A: The Developer provided the notices required by CDD guidelines:
  - all abutters and abutters to abutters received direct notice by mail.
  - We sent copies of our notice to each of the Fresh Pond Residents
     Association, the North Cambridge Stabilization Committee and Friends of
     Alewife, and asked them to invite their members.
  - We provided CDD staff with notice of the meeting.
  - Residential buildings near the Project site were notified through building management.

We also sent the following additional notifications:

- We sent emails and notices to individuals who attended to Project's Conservation Commission hearing.
- We published notice of the meeting in the Cambridge Chronicle.