



City of Cambridge, Massachusetts

Department of Public Works

147 Hampshire Street • Cambridge, MA 02139

APPENDIX E

DRAFT


Example Calculation for

Water Quality Control

Runoff Volume

January 2008

Version 1/21/08



Report Prepared By:

Cambridge Department of Public Works and

Malcolm Pirnie, Inc.

601 Edgewater Drive

Suite 360

Wakefield, MA 01880

781-224-4488

5400001

DRAFT

PAGE INTENTIONALLY LEFT BLANK

This is nonprinting text.
DO NOT DELETE THIS TEXT OR THE SECTION BREAK THAT FOLLOWS
(Click ¶ button on Formatting toolbar to display section breaks)

DRAFT



E. EXAMPLE CALCULATION FOR WATER QUALITY CONTROL RUNOFF VOLUME

Example:

Pre-development condition - 10 acres of pavement and roof

Post-development condition - 2.5 acres of permeable area, 3.0 acres roof (50% green – type 2 technology), 4.5 acres of pavement

Initial *roof runoff* volume requiring treatment = 3.0 ac * 0.5 inch = 1.5 ac-inch.

→ Initial abstraction of water due to vegetation on green roof = 0.3 inches * 1.5 ac = 0.45 ac-inch

→ Infiltration into post-development permeable area: 2.5 ac * 0.085 inches = 0.21 ac-inch

Adjusted *roof runoff* volume requiring water quality treatment = 1.5 ac-inch – 0.45 ac-inch - 0.21 ac-inch = 0.84 ac-inch

Pavement runoff volume requiring treatment = 0.5 ac-inch * 4.5 ac = 2.25 ac-inch

Total net runoff volume (roof + pavement) requiring water quality treatment = 0.84 ac-inch + 2.25 ac-inch = 3.09 ac-inch

Note that the system used to satisfy the stormwater retention requirement of between the 2-year and 25-year storm may also be used to offset the water quality volume requiring treatment, providing it satisfies the other stormwater quality treatment requirements.

This is nonprinting text.

DO NOT DELETE THIS TEXT OR THE SECTION BREAK THAT FOLLOWS
(Click ¶ button on Formatting toolbar to display section breaks)